

1.50mm

(0.059") PITCH CONNECTOR



Material

I/NO	DESCRIPTION	MATERIAL
1	HOUSING	NYLON 66, UL94V-0

**Wire to Board
Connectors**

Housing

Available Pin

PARTS NO.	A	B	C
15001HS-02	4.5	3.3	1.5
15001HS-03	6.0	4.8	3.0
15001HS-04	7.5	6.3	4.5
15001HS-05	9.0	7.8	6.0
15001HS-06	10.5	9.3	7.5
15001HS-07	12.0	10.8	9.0
15001HS-08	13.5	12.3	10.5
15001HS-09	15.0	13.8	12.0
15001HS-10	16.5	15.3	13.5
15001HS-11	18.0	16.8	15.0
15001HS-12	19.5	18.3	16.5
15001HS-13	21.0	19.8	18.0

Specification

ITEM	SPEC
Voltage Rating	AC/DC 250V
Current Rating	AC/DC 1A
Operating Temperature	-25°C ~ +85°C
Contact Resistance	30mΩ MAX
Withstanding Voltage	AC500V/1min
Insulation Resistance	500MΩ MIN
Applicable Wire	AWG #26~#28
Applicable P.C.B	-
Applicable FPC/FFC	-
Solder Height	-
Crimp Tensile Strength	-
UL FILE NO	-

◆ *Applicable Terminal : 15001TS*

